



KEY FACTS

- Available in different sizes suitable for the carrier vehicle.
- Proper and simple connection.
- Plug-and-crack connection.
- Easy supply of the pre-split material to chippers.
- Robust and proven technology –
Low-wear and low-service.
- KTL-primed (cathodic dip-coating) and powder coating.
Made of high-strength Hardox® steel.



endlessly rotatable Rotator for flexible application



TECHNICAL DATA



PATENTED

| WOODCRACKER® W | W 600 | W 820 | W 1000 | W 1350 | W 1800 |
|---|-----------|-----------|-----------|-----------|------------------|
| Tongs opening (mm) | 620 | 820 | 1040 | 1370 | 1830 |
| Splitting force at 240 bar (t) | 26 | 26 | 26 | 34 | 47 ³⁾ |
| Deadweight (Base – Full equipment) (kg) | 310 | 370 | 580 | 990 | 1990 |
| Recommended pump flow capacity (l/min.) | 25 - 60 | 25 - 60 | 40 - 80 | 80 - 150 | 100 - 190 |
| Recommended operating pressure (bar) | 190 - 250 | 190 - 250 | 190 - 250 | 220 - 270 | 240 - 300 |
| Service weight of carrier vehicle (t) | 6 | 10 | 14 | 20 | 30 |
| Roller system | • | • | - | - | - |
| Optional: Autospeed | • | • | • | - | - |
| Optional: Rotator | • | • | • | • | • |

Technical data and illustrations are not binding. Subject to changes for reasons of further development.

APPLICATION AREAS

- Splitting thick wood trunks with minimal effort.
- Can be used in all harvesting and processing methods of strong wood.
- Pre-splitting wood allows a natural drying process and as a result an increase in biomass quality and energy yield.
- Splitting tongs can be used as a gripper.
- Pre-splitting wood for further processing of split logs or chipped wood material.
- Easy supply of the pre-split material to chippers.



Easy supply of the pre-split material to chippers.



Splitting thick wood trunks with minimal effort.



Pre-splitting wood allows a natural drying process.



Various mounting options.

¹⁾ Depending on operating mode or equipment. ²⁾ Depending on specifications of the operation vehicle. ³⁾ At 300 bar working pressure.
• available - not available